

Product Features :

- 4.2" High Speed Color Mini Dome
- 10X Optical Zoom 3.8~38mm Lens
- 500 TVL 0.02LUX
- Wall / Ceiling Bracket Included
- Blower Built-in
- DC12V
- Dimension 120 x 160mm
- Pelco-D Compatible



Video :

Optical Technology Base:	COLOR 1/4" CCD
Effective Pixels:	EIA/NTSC: 786(H) x 494(V) / 752(H) x 582(V)
Angle Field of View:	H: Approx. 51.2" (WIDE) to 5.58" (TELE) / V: Approx. 39.3" (WIDE) to 4.27"(TELE)
Picture Elements (Horz x Vert in mm):	EIA/NTSC: 811H x 508V - CCIR/PAL: 795H x 596V
Scanning System:	2:1 Interlace
Sync System:	Internal / VD-Lock
Resolution:	500TVL (COLOR) / 570TVL (B/W)
Minimum Illumination:	0.7 Lux (F1.8, COLOR) 0.02 Lux (F1.8, B/W) / IR CUT
White Balance:	ATW / AWB / FIX (zero color rolling)
White Balance Range:	1800°K to 10500K°
B.L.C Function :	Super BLC, 48 zone BLC
Gamma Correction :	0.45/1
AGC:	Auto (18dB max)
ALC:	AUTO / FIX
Image Negative :	Select by OSD menu
Motion Detect :	48 zones (select by OSD)
Electronic Shutter :	AES:1/60(1/50)~1/120.000sec./ Manual:8Step
Lens:	10X Optical Zoom Lens, F1.8(W)~2.9(T), f=3.8mm(W)~38mm(T)
Focus:	Auto/Manual
Mirror Function:	Vertical / Horizontal

PTZ:

Baud rate:	(2400/4800/9600/19200bps)
Communication Protocol:	Pelco-D, Pelco-P
ID Setting:	0~255
Decoder:	Built-in
Pan Rotation:	360°
Tilt Rotation:	Tilt 90°~200°/s w/ auto flip
Rotation Speed:	Pan 1°~200°/s Tilt 1°~150°/s
Preset:	128
Tours:	Preset / hour / scan / pattern

Operational Temperature :	-10°C - +50°C
Environment Humidity :	0~75% (no condensation)
Bracket :	Ceiling mount / Wall mount
Weight :	2.42 Lbs

Power:

Power Supply:	DC12V
Power Consumption:	9W

Dimensions(mm):	120mm x 160mm
------------------------	---------------

* Pictures and specifications are subject to change without prior notice

E)