ULTRA-HIGH 700TVL RESOLUTION, DAY / NIGHT, MINI-VANDAL DOME CAMERA

MINI-VANDAL DOME VDM700DN

- Ultra-High, 700TVL Resolution
- ▶ 1/3" Sony Exview HAD CCD II
- Digital Day / Night Functionality for Low Light Conditions
- 3.6mm Fixed Lens
- Minimum Scene Illumination of 0.05 Lux (Color) @ F2.0
- 2D-DNR (Digital Noise Reduction) Technology for Increased Picture Quality and Smaller Recorded Digital File Sizes
- ▶ IP67 Weatherproof Rated, Vandal Resistant Housing
- 3-Axis Gimbal Adjustment
- 12VDC Power Source





SPECIFICATIONS

| MODEL | | VDM700DN |
|------------------|---------------------------|---------------------------------|
| GENERAL | Signal Format | NTSC |
| | Image Device | 1/3" Sony Exview HAD CCD II |
| | Scanning Frequency | H:15.734KHz, V:59.94Hz |
| | Total Pixels | 1020(H) x 508(V) |
| | Effective Pixels | 976(H) x 494(V) |
| | IP rating | IP67 |
| | Electronic Shutter | 1/60 ~ 1/100,000sec |
| | Sync System | Internal |
| | Scanning System | 2 : 1 Interlace |
| V D E O | H.Resolution | 700TV Lines |
| | S/N Ratio | More than 50dB(AGC Off) |
| | Gamma | r =0.45 |
| | Video Output | 1.0 Vp-p Composite $75(\Omega)$ |
| M E C H A N - C | | |
| | Lens | Board |
| | Operating Temperature | 14°F~122°F (-10°C~+50°C) |
| | Storage Temperature | -4°F~140°F (-20°C~+60°C) |
| | Min.Illumination | 0.05 Lux / F2.0 |
| | Operating Humidity | Less than 80% |
| | Input Power Source | DC 12V (±10%) Max 110mA |
| A | Dimensions (DIA x H) | 3.2 x 2.5in (82.2 x 63.6mm) |
| | | |
| | Conformity Certifications | FCC |

DIMENSIONS

