





Catalog Number UPC Number Description

60198673022 Exit Sign LED Remote Capable

73022

Red Letters White Housing

- Features Superior Quality Exit Unit Combined with LED Energy Saving Technology
 - Completely Self-Contained
 - Fully Automatic Operation
 - Compact, Low Profile Design in Neutral Finish
 - Push to Test Switch in Battery Backup Units
 - Automatic, Low Voltage Disconnect (LVD)
- 120 or 277 VAC Operation
- Injection-Molded, UL 94 V-0 Flame Retardant, High Impact Housing
- Charge Rate/Power On LED Indicator Light
- Energy Consumption of Less than 4 Watts for Red Letters
- and Less than 2 Watts for Green Letters
- Listed for Damp Location
- Universal Mounting Canopy & 2 Face Plates for Side or
- Top Installation
- Standard AC and Emergency Units Available
- 700MAH 4.8V Ni-CAD Battery On Battery Backup Units
- Remote Capable
- 4 Lamps 90 Minute Battery Run Time
- 3 Lamps 120 Minute Battery Run Time
- 2 Lamps 180 Minute Battery Run Time

Dimension Information

L Inches	12.00
H Inches	7.50
Depth Inches (mm)	1.50

Specifications

1.5

Input Rating Amps:	18.1 mA @120V, 7.76 mA @ 277V
Input Rating Watts:	1.64W @ 120V 1.60W @ 277V
Frequency:	60 Hz
Voltage Rating:	120/277
Flammability Rating:	UL94V-0
Battery Operation:	4.8 Volt 4.5 AH Lead Acid - 90 Minutes Min

Packaging	
Box Qty	

F

1 Master Carton Qty 6

Certifications 111

01	01 324
cUL	No
RoHS	Yes

111 924