




Catalog Number 73016
UPC Number 60198673016
Description Exit Sign
LED
Green Letters White Housing



Features

- Superior Quality Exit Unit Combined with LED Energy Saving Technology
- Completely Self-Contained
- Fully Automatic Operation
- Compact, Low Profile Design in Neutral Finish
- Push to Test Switch in Battery Backup Units
- Automatic, Low Voltage Disconnect (LVD)
- 120 or 277 VAC Operation
- Injection-Molded, UL 94 V-0 Flame Retardant, High Impact Housing
- Charge Rate/Power On LED Indicator Light
- Energy Consumption Less than 4 W Red Legend 2 W Green legend
- Listed for Damp Location
- Universal Mounting Canopy & 2 Face Plates for Side or Top Installation
- Standard AC and Emergency Units Available
- 700MAH 4.8V Ni-CAD Battery On Battery Backup Units
- 90 Minute Battery Run Time

Dimension Information

L Inches 12.00
H Inches 7.50
Depth Inches (mm) 1.50

Specifications

Input Rating Amps: 18.1 mA @ 120V, 7.76 mA @ 277V
Input Rating Watts: 1.64W @ 120V 1.60W @ 277V
Frequency: 60 Hz
Voltage Rating: 120/277
Flammability Rating: UL94V-0
Battery Operation: 4.8 Volt 4.5 AH Lead Acid - 90 Minutes Min

Packaging

Box Qty 1
Master Carton Qty 6

Certifications

UL UL 924
cUL No
RoHS Yes